

2:1 Crack Injection

TABLE 1: Crack injection usage estimating guide **CRACKBOND LR-321, LR-321G, LR-321LPL and SLV-302**^{1,2,3}

Approximate Coverage Rates Linear Feet (Linear Meters)					
Crack Width in. (cm)	Crack Depth in. (cm)	Packaging Size			
		6 fl. oz. (177 ml)	16 fl. oz. (473 ml)	102 fl. oz. (3.2 L)	15 Gal (56.8L)
1/400 in. or 0.0025 (0.006)	4 (10.2)	75.2 (22.9)	225.6 (68.8)	1,534 (467.6)	28,876 (8,801)
	6 (15.2)	50.1 (15.3)	150.4 (45.8)	1,023 (311.7)	19,250 (5867.5)
	8 (20.3)	37.6 (11.5)	112.8 (34.4)	767 (233.8)	14,438 (4400.6)
	10 (25.4)	30.1 (9.2)	90.2 (27.5)	614 (187.0)	11,550 (3520.5)
1/200 in. or 0.0050 (0.013)	4 (10.2)	37.6 (11.5)	112.8 (34.4)	767 (233.8)	14,438 (4,401)
	6 (15.2)	25.1 (7.6)	75.2 (22.9)	511 (155.9)	9,625 (2933.8)
	8 (20.3)	18.8 (5.7)	56.4 (17.2)	384 (116.9)	7,219 (2200.3)
	10 (25.4)	15.0 (4.6)	45.1 (13.8)	307 (93.5)	5,775 (1760.3)
1/64 in. or 0.0156 (0.040)	4 (10.2)	12.1 (3.7)	36.2 (11.0)	246 (74.9)	4,628 (1,410)
	6 (15.2)	8.0 (2.4)	24.1 (7.3)	164 (50.0)	3,085 (940.3)
	8 (20.3)	6.0 (1.8)	18.1 (5.5)	123 (37.5)	2,314 (705.2)
	10 (25.4)	4.8 (1.5)	14.5 (4.4)	98 (30.0)	1,851 (564.2)
1/32 in. or 0.0313 (0.079)	4 (10.2)	6.0 (1.8)	18.0 (5.5)	123 (37.4)	2,310 (704)
	6 (15.2)	4.0 (1.2)	12.0 (3.7)	82 (24.9)	1,540 (469.4)
	8 (20.3)	3.0 (0.9)	9.0 (2.8)	61 (18.7)	1,155 (352.1)
	10 (25.4)	2.4 (0.7)	7.2 (2.2)	49 (15.0)	924 (281.6)
1/16 in. or 0.0625 (0.159)	4 (10.2)	3.0 (0.9)	9.0 (2.8)	61 (18.7)	1,155 (352)
	6 (15.2)	2.0 (0.6)	6.0 (1.8)	41 (12.5)	770 (234.7)
	8 (20.3)	1.5 (0.5)	4.5 (1.4)	31 (9.4)	578 (176.0)
	10 (25.4)	1.2 (0.4)	3.6 (1.1)	25 (7.5)	462 (140.8)
1/8 in. or 0.1250 (0.318)	4 (10.2)	1.5 (0.5)	4.5 (1.4)	31 (9.4)	578 (176)
	6 (15.2)	1.0 (0.3)	3.0 (0.9)	20 (6.2)	385 (117.4)
	8 (20.3)	0.8 (0.2)	2.3 (0.7)	15 (4.7)	289 (88.0)
	10 (25.4)	0.6 (0.2)	1.8 (0.6)	12 (3.7)	231 (70.4)

1. Values are approximate and may vary depending on waste, concrete and user technique.

2. Capping cracks using Miracle Bond 1310 in a 9 oz. cartridge, will cap approximately 7 linear feet (2.1 linear meters) of a crack, with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.

3. Capping cracks using EPOXY REPAIR PASTE in a 21.2 oz. cartridge, will cap approximately 16 linear feet (4.8 linear meters) of a crack, with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.