

TABLE 1: Crack repair usage estimating guide for CRACKBOND CSR¹

Approximate Coverage Rates Linear Feet (Linear Meters)				
Crack Width in. (cm)	Crack Depth in. (cm)	Package Size		
		8.6 fl. oz. (254 ml)	21.2 fl. oz. (627 ml)	2 Gal (7.6 L)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	77.0 (23.5)	202.1 (61.6)	2,464 (751)
	0.375 (1.0)	51.3 (15.6)	134.8 (41.1)	1,643 (500.7)
	0.5 (1.3)	38.5 (11.7)	101.1 (30.8)	1,232 (375.5)
	0.75 (1.9)	25.7 (7.8)	67.4 (20.5)	821 (250.3)
1/8 in. or 0.1250 (0.318)	0.25 (0.6)	38.5 (11.7)	101.1 (30.8)	1,232 (376)
	0.375 (1.0)	25.7 (7.8)	67.4 (20.5)	821 (250.3)
	0.5 (1.3)	19.3 (5.9)	50.5 (15.4)	616 (187.8)
	0.75 (1.9)	12.8 (3.9)	33.7 (10.3)	411 (125.2)
3/16 in. or 0.1875 (0.476)	0.25 (0.6)	25.7 (7.8)	67.4 (20.5)	821 (250)
	0.375 (1.0)	17.1 (5.2)	44.9 (13.7)	548 (166.9)
	0.5 (1.3)	12.8 (3.9)	33.7 (10.3)	411 (125.2)
	0.75 (1.9)	8.6 (2.6)	22.5 (6.8)	274 (83.4)
1/4 in. or 0.25 (0.635)	0.25 (0.6)	19.3 (5.9)	50.5 (15.4)	616 (188)
	0.375 (1.0)	12.8 (3.9)	33.7 (10.3)	411 (125.2)
	0.5 (1.3)	9.6 (2.9)	25.3 (7.7)	308 (93.9)
	0.75 (1.9)	6.4 (2.0)	16.8 (5.1)	205 (62.6)
3/8 in. or 0.3750 (0.953)	0.25 (0.6)	12.8 (3.9)	33.7 (10.3)	411 (125)
	0.375 (1.0)	8.6 (2.6)	22.5 (6.8)	274 (83.4)
	0.5 (1.3)	6.4 (2.0)	16.8 (5.1)	205 (62.6)
	0.75 (1.9)	4.3 (1.3)	11.2 (3.4)	137 (41.7)
1/2 in. or 0.50 (1.270)	0.25 (0.6)	9.6 (2.9)	25.3 (7.7)	308 (94)
	0.375 (1.0)	6.4 (2.0)	16.8 (5.1)	205 (62.6)
	0.5 (1.3)	4.8 (1.5)	12.6 (3.9)	1,540 (469.4)
	0.75 (1.9)	3.2 (1.0)	8.4 (2.6)	103 (31.3)

1. Values are approximate and may vary depending on waste, concrete and user technique.