

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

#### 1. Product and Company Identification

**Product Name:** Lockable Dowel

**Product Use:** Anchoring & Doweling

**Company Identification:**  
 ADHESIVES TECHNOLOGY CORP.  
 450 East Copans Road  
 Pompano Beach, FL 33064  
 Contact Phone: 1.800.892.1880  
 (9:00a.m. – 5:00p.m. EST)

**Emergency Phone:**  
 Chem-Tel:  
 1.800.255.3924 (24hrs)

#### 2. Hazards Identification (Part A)

##### GHS Classification

Health	Physical	Environmental
Skin Irritant Cat 2 Eye Irritant Cat 2B Skin Sens 1 Carcinogen Cat 2	Not Determined	Toxic to Aquatic Life Cat-2

GHS Label:

##### Warning:



Eye Irritant  
 Skin Irritant  
 Skin Sensitizer

##### Emergency Overview

Causes skin and eye irritation  
 May cause skin sensitization  
 May cause cancer  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

##### **Primary Route of Exposure**

Eyes, skin and oral

##### **Carcinogenicity**

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

does not pose a dust hazard; therefore, **this classification is not relevant.** (Note: sanding of this product will create a possible dust hazard).

#### 3. Composition/ Information on Ingredients (Part A)

<u>CAS Number</u>	<u>Content %</u>	<u>Chemical Name</u>
25068-38-6	40 - 60	Bisphenol A Epoxy Resin
13463-67-7	0.5 - 1.5	Titanium Dioxide
Proprietary	40 - 60	Non-Hazardous

#### 4. First Aid Measures (Part A)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

#### 5. Fire Fighting Measures (Part A)

Flash Point: N/D

Flammable Limits: N/D

##### Extinguisher Media

Carbon Dioxide, Dry Chemical, Water Fog

##### Unusual Fire and Explosion Hazard

None known. Thermal Decomposition can be formed.

##### Special Fire Fighting Procedures

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

#### 6. Accidental Release Measures (Part A)

##### Personal Precautions:

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

##### Environmental Precautions

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

---

#### 7. Handling and Storage (Part A)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

---

#### 8. Exposure Control and Personal Protection (Part A)

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

##### Personal Protective Equipment

###### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

###### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

###### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

###### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

---

#### 9. Physical and Chemical Properties (Part A)

Appearance:	White Paste
Evaporation Rate:	N/D
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	N/D
Vapor Density(air = 1):	Non-volatile
Vapor Pressure:	N/D
VOC Content:	See section 9 of part B for VOC content
pH:	N/D
Boiling Point:	N/D

---

#### 10. Stability and Reactivity (Part A)

Stability: Stable

Thermal Decomposition: Can yield CO, CO<sub>2</sub> and organic Nitrogen compounds.

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

---

Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

#### 11. Toxicological Information (Part A)

**Acute Oral Toxicity:**

Not Determined

**Acute Dermal Toxicity:**

Not Determined.

**Acute Inhalation Toxicity:**

Not Determined

**Skin Irritation:**

Irritating to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Irritating to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Not Determined

**Sensitization:**

May cause allergic skin reaction

The product has not been tested. The statement has been derived from the properties of the individual components.

**STOT – single exposure**

Not Determined

**STOT – Repeated Exposure**

Not Determined

**Carcinogenicity Classification:**

**Titanium Dioxide:**

IARC Group 2B: Possibly carcinogenic to humans.

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

---

**Safety Data Sheet**  
**Lockable Dowel**

Created On: 02/28/2015  
 Revision Date: 04/06/2016  
 Version: 3.0

**12. Ecological Information (Part A)**

**Fish:**

Bisphenol A:  
 Fathead minnow/LC50 (96hrs): >3.1mg/l

**Aquatic Invertebrates:**

Bisphenol A:  
 Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

**Algae:**

No Data Available

**Microorganisms:**

Bisphenol A:  
 Bacteria, (Growth inhibition)/LC50 (18hrs): > 42.6mg/l

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

**13. Disposal Considerations (Part A)**

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

**14. Transportation Information (Part A)**

This product is not regulated as a hazardous material for transportation.

**15. Regulatory Information (Part A)**

HMIS Rating	
Health	2*
Flammability	1
Physical Hazard	0
PPE	B



**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

CERCLA RQ

SARA Title 311/312

Not Determined

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

CA Prop 65

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

TSCA

Listed or Exempt

#### State Regulations:

State RTK  
NJ, MA, PA

CAS#  
25068-38-6  
13463-67-7  
64741-65-7

Chemical Name  
Bisphenol A Epoxy Resin  
Titanium Dioxide  
Naphtha (Petroleum)

## 16. Other Information (Part A)

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

#### 1. Product and Company Identification

**Product Name:** Lockable Dowel (Part B)

**Product Use:** Anchoring & Doweling

**Company Identification:**  
 ADHESIVES TECHNOLOGY CORP.  
 450 East Copans Road  
 Pompano Beach, FL 33064  
 Contact Phone: 1.800.892.1880  
 (9:00a.m. – 5:00p.m. EST)

**Emergency Phone:**  
 Chem-Tel:  
 1.800.255.3924 (24hrs)

#### 2. Hazards Identification (Part B)

##### GHS Classification

Health	Physical	Environmental
Skin Corrosion Cat 1 Serious Eye Damage Cat 1 Acute Tox Dermal/Inhalation Cat 4	Not Determined	Toxic to Aquatic Life Cat-2

GHS Label:

**Danger:**



Skin Sensitizer



Corrosive to skin and eyes

##### **Emergency Overview**

Causes skin burns

Causes serious eye damage

May cause skin sensitization

Harmful if inhaled

Harmful in contact with skin

Wash skin thoroughly after handling

Avoid breathing fume/gas/mist/vapors/spray

Wear protective gloves/ protective clothing/ eye protection/ face protection

Use outdoors or in a well-ventilated area

Avoid contact during pregnancy/while nursing

##### **Primary Route of Exposure**

Eyes, skin and oral

##### **Carcinogenicity**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

#### 3. Composition/ Information on Ingredients (Part B)

<u>CAS Number</u>	<u>Content%</u>	<u>Chemical Name</u>
68953-36-6	40 - 60	Polyamide Resin
90-72-2	7 - 15	Tris-2,4,6(dimethylaminomethyl)phenol
100-51-6	7 - 15	Benzyl Alcohol
140-31-8	1 - 5	N- Aminoethylpiperazine
112-24-3	1 - 5	Triethylenetetramine
Proprietary	15 - 30	Non - Hazardous

#### 4. First Aid Measures (Part B)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

#### 5. Fire Fighting Measures (Part B)

Flash Point: N/D

Flammable Limits: N/D

##### Extinguisher Media

Carbon Dioxide, Dry Chemical, Water Fog

##### Unusual Fire and Explosion Hazard

None known. Thermal Decomposition can be formed.

##### Specific Methods

In the event of fire and/or explosion do not breathe fumes. Use water spray to cool unopened containers.

##### Special Fire Fighting Procedures

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

#### 6. Accidental Release Measures (Part B)

##### Personal Precautions:

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

##### Environmental Precautions

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.



## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

#### 7. Handling and Storage (Part B)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

#### 8. Exposure Control and Personal Protection (Part B)

##### Exposure Guidelines

Component	CAS#	OSHA PEL	TLV
Benzyl Alcohol	100-51-6	50ppm (Ceiling)	100 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

##### Personal Protective Equipment

###### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

###### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

###### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

###### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

#### 9. Physical and Chemical Properties (Part B)

Appearance:	Black Paste
Evaporation Rate:	N/D
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	N/D
Vapor Density(air = 1):	N/D
Vapor Pressure:	N/D
VOC Content:	2 g/L (tested per EPA CFR 40, Part 60, method 24)
pH:	N/D
Boiling Point:	N/D

## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

---

#### 10. Stability and Reactivity (Part B)

Stability:	Stable
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

#### 11. Toxicological Information (Part B)

**Acute Oral Toxicity:**

Not Determined

**Acute Dermal Toxicity:**

Not Determined

**Acute Inhalation Toxicity:**

May cause acute toxicity through inhalation

The product has not been tested. The statement has been derived from the properties of the individual components.

**Skin Irritation:**

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Carcinogenicity Classification:**

No known carcinogens.

---

## Safety Data Sheet Lockable Dowel

Created On: 02/28/2015  
Revision Date: 04/06/2016  
Version: 3.0

### 12. Ecological Information (Part B)

**Acute Toxicity for:**

**Fish:**

Polyamide Resin:

Zebrafish /LC50 (96hrs): >5.0mg/l

**Aquatic Invertebrates:**

Polyamide Resin:

Water Flea Daphnis/EC 50 (48hrs): > 7.07mg/l

**Algae:**

No Data Available

**Microorganisms:**

No Data Available

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure is the air or water will arise.

### 13. Disposal Considerations (Part B)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

### 14. Transportation Information (Part B)

**DOT (US)**

**CARTRIDGE:** Limited Quantity, LTD QTY

**\*BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

\*Bulk packaging in quantities of 1.3 gallons (net) or less are packaged in accordance with the limited quantity exception.

**IATA/ICAO**

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

**IMDG**

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

### 15. Regulatory Information (Part B)

HMIS Rating	
Health	*2
Flammability	1
Physical Hazard	0
PPE	B

**NFPA Rating**



## Safety Data Sheet

### Lockable Dowel

Created On: 02/28/2015

Revision Date: 04/06/2016

Version: 3.0

---

**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

#### Federal Regulations

SARA Title 311/312

Chronic Health Hazard

CA Prop 65

Not Regulated

TSCA

Listed

#### State Regulations:

State RTK  
NJ, MA, PA

CAS#  
140-31-8

Chemical Name  
n-aminoethylpiperazine

---

## 16. Other Information

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.