

**Safety Data Sheet**  
**ULTRABOND® 2100-1**

Created On: 04/03/2015  
 Revision Date: 04/16/16  
 Version: 3.0

**1. Product and Company Identification**

**Product Name:** ULTRABOND 2100-1 (Part A)

**Product Use:** Bonding and Coating

**Company Identification:**  
 ADHESIVES TECHNOLOGY CORP.  
 450 East Copans Road  
 Pompano Beach, FL 33064  
 Contact Phone: 1.800.892.1880  
 (9:00a.m. – 5:00p.m. EST)

**Emergency Phone:**  
 Chem-Tel:  
 1.800.255.3924 (24hrs)

**2. Hazards Identification (Part A)**

**GHS Classification**

Health	Physical	Environmental
Skin Irritant Cat 2 Eye Irritant Cat 2B Carcinogen Cat 2	Not Classified	Toxic to Aquatic Life Cat-2

GHS Label:

**Warning:**



Eye Irritant  
Skin Irritant



Possible Carcinogen

**Emergency Overview**

May cause skin sensitization  
 Causes skin and eye irritation  
 May cause cancer  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

### 3. Composition/ Information on Ingredients (Part A)

<u>CAS Number</u>	<u>Content%</u>	<u>Chemical Name</u>
25085-99-8	60 - 100	Diglycidyl Ether of Bisphenol A
17557-23-2	7 - 15	Neopentyl glycol diglycidyl ether
13463-67-7	0.1 - 1	Titanium Dioxide
64741-65-7	0.1 - 1	Naphtha, Heavy Alkylate

### 4. First Aid Measures (Part A)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

### 5. Fire Fighting Measures (Part A)

Flash Point: 204 °C (>400 °F)

Flammable Limits: N/A

#### **Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

#### **Unusual Fire and Explosion Hazard**

None known. Thermal Decomposition can be formed.

#### **Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

### 6. Accidental Release Measures (Part A)

#### **Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

#### **Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

### 7. Handling and Storage (Part A)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature ranges in between 4 °C and 35 °C (40°F and 95° F).

### 8. Exposure Control and Personal Protection (Part A)

#### Exposure Guidelines

Component	CAS#	OSHA PEL	TLV
Titanium Dioxide	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

#### Personal Protective Equipment

##### **Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

##### **Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

##### **Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

##### **Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

### 9. Physical and Chemical Properties (Part A)

Physical State:	Liquid
Appearance:	White Liquid
Evaporation Rate:	N/D
Odor:	Slight Odor
Odor Threshold:	N/D
Melting/Freezing Point:	N/D
Boiling Point and Range	N/D
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	1.1
Vapor Density(air = 1):	N/D
Vapor Pressure:	N/D
VOC Content:	See section 9 of part B for VOC content
pH:	N/D
Boiling Point:	N/D

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

---

### 10. Stability and Reactivity (Part A)

Stability:	Stable
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

### 11. Toxicological Information (Part A)

Not Determined

**Acute Dermal Toxicity:**

Not Determined

**Acute Inhalation Toxicity:**

Not Determined

**Skin Irritation:**

Irritating to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Irritating to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

**STOT – single exposure**

Not Determined

**STOT – Repeated Exposure**

Not Determined

**Carcinogenicity Classification:**

**Titanium Dioxide:**

IARC Group 2B: Possibly carcinogenic to humans.

**Safety Data Sheet**  
**ULTRABOND® 2100-1**

Created On: 04/03/2015  
 Revision Date: 04/16/16  
 Version: 3.0

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**12. Ecological Information (Part A)**

**Fish:**

Diglycidyl Ether of Bisphenol A:  
 Fathead minnow/LC50 (96hrs): >3.1mg/l

**Aquatic Invertebrates:**

Diglycidyl Ether of Bisphenol A:  
 Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

**Algae:**

No Data Available

**Microorganisms:**

Diglycidyl Ether of Bisphenol A:  
 Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

**13. Disposal Considerations (Part A)**

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

**14. Transportation Information (Part A)**

This product is not regulated as a hazardous material for transportation.

**15. Regulatory Information (Part A)**

HMIS Rating	
Health	2
Flammability	1
Physical Hazard	0
PPE	B



**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme



**Safety Data Sheet**  
**ULTRABOND® 2100-1**

Created On: 04/03/2015  
 Revision Date: 04/16/16  
 Version: 3.0

**1. Product and Company Identification**

**Product Name:** ULTRABOND 2100-1 (Part B)

**Product Use:** Bonding and Coating

**Company Identification:**  
 ADHESIVES TECHNOLOGY CORP.  
 450 East Copans Road  
 Pompano Beach, FL 33064  
 Contact Phone: 1.800.892.1880  
 (9:00a.m. – 5:00p.m. EST)

**Emergency Phone:**  
 Chem-Tel:  
 1.800.255.3924 (24hrs)

**2. Hazards Identification (Part B)**

GHS Classification

Health	Physical	Environmental
Skin Corrosion Cat 1B Serious Eye Damage Cat 1 Carcinogen Cat 1 STOT Cat 2	Not Classified	Toxic to Aquatic Life Cat-2

GHS Label:

**Danger:**



Corrosive to skin and eyes



Carcinogen  
 Possible organ damage

**Emergency Overview**

Causes skin burns  
 Causes severe eye damage  
 May cause cancer  
 May cause damage to organs through prolonged or repeated exposure  
 May be harmful if inhaled  
 Wash skin thoroughly after handling  
 Avoid breathing fume/gas/mist/vapors/spray  
 Wear protective gloves/ protective clothing/ eye protection/ face protection  
 Use outdoors or in a well-ventilated area

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product or one of its ingredients present at 0.1% or more IS listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA.

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

### 3. Composition/ Information on Ingredients (Part B)

<b>CAS Number</b>	<b>Content %</b>	<b>Chemical Name</b>
68953-36-6	20 – 35	Modified Polyamide
90-72-2	1 – 5	Tris-2,4,6(dimethylaminomethyl)phenol
770-35-4	15 - 30	Modified cycloaliphatic Amine
14808-60-7	0.1 – 1	Quartz Silica Sand (Crystalline Silica)
Proprietary	30 – 50	Non Hazardous

### 4. First Aid Measures (Part B)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

### 5. Fire Fighting Measures (Part B)

Flash Point: >93°C (200°F)

Flammable Limits: N/A

#### **Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

#### **Unusual Fire and Explosion Hazard**

None known. Thermal Decomposition can be formed.

#### **Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

### 6. Accidental Release Measures (Part B)

#### **Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

#### **Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.



**Safety Data Sheet**  
**ULTRABOND® 2100-1**

Created On: 04/03/2015  
 Revision Date: 04/16/16  
 Version: 3.0

**7. Handling and Storage (Part B)**

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.  
**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature ranges in between 4 °C and 35 °C (40°F and 95° F).

**8. Exposure Control and Personal Protection (Part B)**

**Exposure Guidelines**

Component	CAS#	OSHA PEL	TLV
Quartz Silica Sand (Crystalline Silica)	14808-60-7	0.1 mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup>

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

**Personal Protective Equipment**

**Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

**9. Physical and Chemical Properties (Part B)**

Appearance: Black Paste  
 Evaporation Rate: N/D  
 Odor: Slight Odor  
 Solubility in Water: Insoluble  
 Specific Gravity(g/cc): N/D  
 Vapor Density: N/D  
 Vapor Pressure: N/D  
 VOC Content: 8 g/L (tested per EPA CFR 40, Part 60, method 24)  
 pH: N/D  
 Boiling Point: N/D

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

---

### 10. Stability and Reactivity (Part B)

Stability:	Stable
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

---

### 11. Toxicological Information (Part B)

**Acute Oral Toxicity:**

Not Determined

**Acute Dermal Toxicity:**

Not Determined

**Acute Inhalation Toxicity:**

Not Determined

**Skin Irritation:**

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause lung irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction and irritation to the respiratory system.

The product has not been tested. The statement has been derived from the properties of the individual components.

**STOT – single exposure**

Not Determined

**STOT – Repeated Exposure**

CNS, Skin

**Carcinogenicity Classification:**

**Quartz Silica Sand (Crystalline Silica):**

IARC Group1: Known human carcinogen based on human evidence.

## Safety Data Sheet ULTRABOND® 2100-1

Created On: 04/03/2015

Revision Date: 04/16/16

Version: 3.0

---

NTP (National Toxicology Program) has classified Crystalline Silica as a known human carcinogen.

---

### 12. Ecological Information (Part B)

**Acute Toxicity for:**

**Fish:**

Polyamide Resin:

Zebrafish /LC50 (96hrs): >5.0mg/l

**Aquatic Invertebrates:**

Polyamide Resin:

Water Flea Daphnis/EC 50 (48hrs): > 7.07mg/l

**Algae:**

No Data Available

**Microorganisms:**

No Data Available

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure is the air or water will arise.

---

### 13. Disposal Considerations (Part B)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

### 14. Transportation Information (Part B)

**DOT (US)**

**CARTRIDGE:** Limited Quantity, LTD QTY

**\*BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

\*Bulk packaging in quantities of 1.3 gallons (net) or less are packaged in accordance with the limited quantity exception.

**IATA/ICAO**

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

**IMDG**

**CARTRIDGE/BULK:** AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III

**Marine pollutant:** No

---

**Safety Data Sheet**  
**ULTRABOND® 2100-1**

Created On: 04/03/2015  
 Revision Date: 04/16/16  
 Version: 3.0

**15. Regulatory Information (Part B)**

HMIS Rating	
Health	*2
Flammability	1
Physical Hazard	0
PPE	G



**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

SARA Title 311/312

Chronic Health Hazard (Bisphenol A)

CA Prop 65

This product does contain a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

TSCA

Listed or Exempt

**16. Other Information**

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, Adhesives Technology Corp. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.