

TABLE 1: MIRACLE BOND REPAIR EPOXY Estimating Guide 1 to 1 CARTRIDGES¹

Approximate Coverage Rates Linear Feet (Linear Meters)		
Crack Width in. (cm)	Crack Depth in. (cm)	Cartridge Size
		8.6 fl. oz. (254 ml)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	77.0 (23.5)
	0.375 (1.0)	51.3 (15.6)
	0.5 (1.3)	38.5 (11.7)
	0.75 (1.9)	25.7 (7.8)
1/8 in. or 0.1250 (0.318)	0.25 (0.6)	38.5 (11.7)
	0.375 (1.0)	25.7 (7.8)
	0.5 (1.3)	19.3 (5.9)
	0.75 (1.9)	12.8 (3.9)
3/16 in. or 0.1875 (0.476)	0.25 (0.6)	25.7 (7.8)
	0.375 (1.0)	17.1 (5.2)
	0.5 (1.3)	12.8 (3.9)
	0.75 (1.9)	8.6 (2.6)
1/4 in. or 0.25 (0.635)	0.25 (0.6)	19.3 (5.9)
	0.375 (1.0)	12.8 (3.9)
	0.5 (1.3)	9.6 (2.9)
	0.75 (1.9)	6.4 (2.0)
3/8 in. or 0.3750 (0.953)	0.25 (0.6)	12.8 (3.9)
	0.375 (1.0)	8.6 (2.6)
	0.5 (1.3)	6.4 (2.0)
	0.75 (1.9)	4.3 (1.3)
1/2 in. or 0.50 (1.270)	0.25 (0.6)	9.6 (2.9)
	0.375 (1.0)	6.4 (2.0)
	0.5 (1.3)	4.8 (1.5)
	0.75 (1.9)	3.2 (1.0)

1. Values are approximate and may vary depending on waste, concrete and user technique.