

Qualified Products List

Spec Reference:
705.20 - Non-Shrink Non-Metallic Material

Source: 72701-01
Adhesives Technologies Corp. -
Pompano Beach, FL

Address: 450 E. Copans Rd.
Pompano Beach, FL 33064

Phone: (954)789-4764

Matl Cd	Material Name	Brand Name	Comments
42609	Non-Shrink Non-Metallic Material	ULTRABOND 1300	INSTALL PER MANUFACTURER'S INSTRUCTIONS @ TEMPERATURE BETWEEN 40 DEGREES F-110 DEGREES F.
42609	Non-Shrink Non-Metallic Material	ULTRABOND ACRYL-8CC	INSTALL PER MANUFACTURER'S INSTRUCTIONS. PER ODOT SPEC, MEETS ASTM C881, Type IV, Grade 3, Class A, B & C
42609	Non-Shrink Non-Metallic Material	ULTRABOND ASF-2000	INSTALL PER MANUFACTURER'S INSTRUCTIONS @ TEMPERATURE BETWEEN 5 DEGREES F - 110 DEGREES F. PER ODOT SPEC, MEETS ASTM C881, Type IV, Grade 3, Class A, B & C
42609	Non-Shrink Non-Metallic Material	ULTRABOND EPX-3CC	INSTALL PER MANUFACTURER'S INSTRUCTIONS @ TEMPERATURE BETWEEN 48 DEGREES F - 108 DEGREES F. PER ODOT SPEC, MEETS ASTM C881, Type IV, Grade 3, Class B & C
42609	Non-Shrink Non-Metallic Material	ULTRABOND HS-1CC	INSTALL PER MFG INSTRUCTIONS FOR CLASS A, B & C - ASTM C881. DO NOT APPLY BELOW 38 DEG F OR ABOVE 125 DEG F AMBIENT TEMP