



BULLETIN 15 (Publication 35) Qualified Products List for Construction

Posted:
5/17/2018 10:45:43AM

516.2(k) Anchor Material

Last Revised: 9/27/2017

See [Standard Drawing RC-26M \(Publication 72M\)](#)

Note: Adhesive anchors are not to be used for permanent installations which have the anchor in tension due to external loading regardless of whether the anchor is in a horizontal or vertical position. External loading can be from moment, moment and shear or direct tension to cause tension in the anchor. Tension due to a torqued bolt is not an external load.

Product	Name	Ref. No.
ADHTC 15 Adhesives Technology Corporation, 450 East Copans, Pompano Beach, FL 33064 http://www.atcepoxy.com/		
Dowel Bar Adhesive	ASF-1000	2016-242Q
Dowel Bar Adhesive	Ultrabond 1300	1992-013B
Dowel Bar Adhesive	ULTRABOND 365CC	2016-017Q
Dowel Bar Adhesive	Ultrabond HS-200	2002-048Q
Dowel Bar Adhesive	Ultrabond HS-1CC	2018-048Q
<i>Cold Weather Formula: Very short working times at warm temperatures.</i>		

Section 643: Temporary Concrete Barrier, Structure Mounted

643.2(c)6 Adhesive Bonding Material (use in accordance with BC-719M)

Last Revised: 3/17/2017

Use in accordance with BC-719M. [Standard Drawing of Temporary Concrete Barrier, Structure Mounted \(Pub 219M, BC-719M\)](#)

Product	Name	Installation Type	Spacing	Ref. No.
ADHTC 15 Adhesives Technology Corporation, 450 East Copans, Pompano Beach, FL 33064 http://www.atcepoxy.com/				
Adhesive Bonding Material	Ultrabond HS-200	A, B	1', 2', 4'	2004-054Q
<i>Provisionally Approved</i>				
Adhesive Bonding Material	Ultrabond HS-200	C	1'	2004-054Q



BULLETIN 15 (Publication 35) Qualified Products List for Construction

Posted:
5/17/2017 10:45:43AM

Section 706: Concrete Bonding Compound

Type I - Non-load bearing applications, bonding hardened concrete (28 days or older) to hardened concrete surfaces

Type II - Non-load bearing applications, bonding freshly mixed concrete to hardened concrete

Type III - For bonding skid-resistant materials to hardened concrete and as a binder in epoxy mortars or epoxy concretes used on traffic bearing surfaces

Type V - Load bearing applications, bonding fresh concrete to hardened concrete

Grade 1 - Low viscosity;

Grade 2 - Medium viscosity;

Grade 3 - Non-sagging consistency

Class A - For use below 40F, to the lowest allowable temperature defined by manufacturer

Class B - For use between 40F and 60F

Class C - For use above 60F, to the highest allowable temperature defined by manufacturer

706.1 Epoxy Bonding Compound (ASTM C881)

Last Revised: 12/14/2016

Product	Name	Epoxy Class	Ref. No.
ADHTC 15	Adhesives Technology Corporation, 450 East Copans, Pompano Beach, FL 33064 http://www.atcepoxy.com/		
Type I, Grade 1	CRACKBOND LR-321	C	2016-101
Type I, Grade 2	Ultrabond 2100		2009-095Q

Section MISC: Miscellaneous

MISC Anchoring Devices for Use in Vertical Positions Only

Last Revised: 8/19/2016

Adhesive anchors are not to be used for permanent installations which have the anchor in tension due to external loading regardless of whether the anchor is in a horizontal or vertical position.

External loading can be from moment, moment and shear, or direct tension to cause tension in the anchor. Tension due to a torqued bolt is not an external load. See Section 516.2(k) for horizontal anchoring applications. Steel Products Procurement Act applies for mechanical anchors and threaded rods.

Product	Name	Ref. No.
ADHTC 15	Adhesives Technology Corporation, 450 East Copans, Pompano Beach, FL 33064 http://www.atcepoxy.com/	
Anchoring Adhesive	Ultrabond HS-200	2002-048Q



BULLETIN 15 (Publication 35) Qualified Products List for Construction

Posted:
5/17/2017 10:45:43AM

706.2 Other Bonding Compound (ASTM C882)

Last Revised: 5/11/2017

Product	Name	Ref. No.
ADHTC 15 Adhesives Technology Corporation, 450 East Copans, Pompano Beach, FL 33064 http://www.atcepoxy.com/ Type II, Grade 3, Class A & B	ASF-1000	2016-285Q